



# L7102

## Power Handling

750 Watts RMS / 1500 Watts Max.

**Dual Voice Coil  
Subwoofer 25 cm**

### Technical Specifications

|                       |      |                     |
|-----------------------|------|---------------------|
| Impedance             | Zn   | 2 x 2 Ohms          |
| Voice Coil Diameter   | Ø    | 61 mm               |
| Max. Linear Excursion | Xmax | +/- mm              |
| Cone Area             | Sd   | 439 cm <sup>2</sup> |
| Moving Mass           | Mms  | g                   |
| DC Resistance         | Re   | 2 x 2 Ohms          |
| Resonance Frequency   | Fs   | 37,5 Hz             |
| Mechanical Q-Factor   | Qms  | 9,791               |
| Electrical Q-Factor   | Qes  | 0,535               |
| Total Q-Factor        | Qts  | 0,507               |
| Equivalent Air Volume | VAS  | 28,3 L              |
| VC Inductance         | Le   | mH                  |
| Flux Density          | B/L  | N/A                 |
| Efficiency 1W/1m      | SPL  | 85,9 dB             |

### Recommended Enclosure

|                |                     |
|----------------|---------------------|
| Ported Box     |                     |
| Vented Volume: | 63,7 L              |
| Port Area:     | 220 cm <sup>2</sup> |
| Port Length:   | 46 cm               |

### Recommended Enclosure

|                |                     |
|----------------|---------------------|
| Ported Box     |                     |
| Vented Volume: | 35,4 L              |
| Port Area:     | 185 cm <sup>2</sup> |
| Port Length:   | 50 cm               |

### Mechanical Components

- Diecast Aluminium Basket
- Polypropylene Cone
- Santoprene Surround
- Single Nomex Spider
- Dual Magnet 2 x 59,1 oz (3.351 g)
- Magnet Size: Ø169 x 40 mm
- TIL (Glass-Fibre) Voice Coil

### Dimensions & Weight

|                    |        |
|--------------------|--------|
| External Diameter: | 272 x  |
| Mounting Diameter: | 272 mm |
| Mounting Depth:    | 237 x  |
| Shipping Weight:   | 237 mm |





# L7102

## Power Handling

750 Watts RMS / 1500 Watts Max.

**Dual Voice Coil  
Subwoofer 25 cm**

### Technical Specifications

|                       |      |                     |
|-----------------------|------|---------------------|
| Impedance             | Zn   | 2 x 2 Ohms          |
| Voice Coil Diameter   | Ø    | 61 mm               |
| Max. Linear Excursion | Xmax | +/- mm              |
| Cone Area             | Sd   | 439 cm <sup>2</sup> |
| Moving Mass           | Mms  | g                   |
| DC Resistance         | Re   | 2 x 2 Ohms          |
| Resonance Frequency   | Fs   | 37,5 Hz             |
| Mechanical Q-Factor   | Qms  | 9,791               |
| Electrical Q-Factor   | Qes  | 0,535               |
| Total Q-Factor        | Qts  | 0,507               |
| Equivalent Air Volume | VAS  | 28,3 L              |
| VC Inductance         | Le   | mH                  |
| Flux Density          | B/L  | N/A                 |
| Efficiency 1W/1m      | SPL  | 85,9 dB             |

### Recommended Enclosure

|                |                     |
|----------------|---------------------|
| Ported Box     |                     |
| Vented Volume: | 63,7 L              |
| Port Area:     | 220 cm <sup>2</sup> |
| Port Length:   | 46 cm               |

### Recommended Enclosure

|                |                     |
|----------------|---------------------|
| Ported Box     |                     |
| Vented Volume: | 35,4 L              |
| Port Area:     | 185 cm <sup>2</sup> |
| Port Length:   | 50 cm               |

### Mechanical Components

Former

### Dimensions & Weight

175 mm  
12,8 kg



Audio Design. Tel. 07253-9465-14. Fax 946510. eMail: [boxes@audiodesign.de](mailto:boxes@audiodesign.de). Internet: [www.audiodesign.de](http://www.audiodesign.de)