



L7124

**Dual Voice Coil
Subwoofer 30 cm**

Power Handling
900 Watts RMS / 1800 Watts Max.

Technical Specifications

Impedance	Zn	2 x 4 Ohms
Voice Coil Diameter	Ø	66 mm
Max. Linear Excursion	Xmax	+/- mm
Cone Area	Sd	645 cm ²
Moving Mass	Mms	g
DC Resistance	Re	2 x 3,4 Ohms
Resonance Frequency	Fs	34 Hz
Mechanical Q-Factor	Qms	9,488
Electrical Q-Factor	Qes	0,571
Total Q-Factor	Qts	0,539
Equivalent Air Volume	VAS	54,3 L
VC Inductance	Le	mH
Flux Density	B/L	N/A
Efficiency 1W/1m	SPL	86,9 dB

Recommended Enclosure

Ported Box	
Vented Volume:	92 L
Port Area:	258 cm ²
Port Length:	37 cm

Recommended Enclosure

Ported Box	
Vented Volume:	49,6 L
Port Area:	217 cm ²
Port Length:	57 cm

Mechanical Components

- Diecast Aluminium Basket
- Polypropylene Cone
- Santoprene Surround
- Single Nomex Spider
- Dual Magnet 2 x 62,3 oz (3.532 g)
- Magnet Size: Ø170 x 40 mm
- TIL (Glass-Fibre) Voice Coil

Dimensions & Weight

External Diameter:	320 x
Mounting Diameter:	320 mm
Mounting Depth:	281 x
Shipping Weight:	281 mm





L7124

**Dual Voice Coil
Subwoofer 30 cm**

Power Handling
900 Watts RMS / 1800 Watts Max.

Technical Specifications

Impedance	Zn	2 x 4 Ohms
Voice Coil Diameter	Ø	66 mm
Max. Linear Excursion	Xmax	+/- mm
Cone Area	Sd	645 cm ²
Moving Mass	Mms	g
DC Resistance	Re	2 x 3,4 Ohms
Resonance Frequency	Fs	34 Hz
Mechanical Q-Factor	Qms	9,488
Electrical Q-Factor	Qes	0,571
Total Q-Factor	Qts	0,539
Equivalent Air Volume	VAS	54,3 L
VC Inductance	Le	mH
Flux Density	B/L	N/A
Efficiency 1W/1m	SPL	86,9 dB

Recommended Enclosure

Ported Box	
Vented Volume:	92 L
Port Area:	258 cm ²
Port Length:	37 cm

Recommended Enclosure

Ported Box	
Vented Volume:	49,6 L
Port Area:	217 cm ²
Port Length:	57 cm

Mechanical Components

Former

Dimensions & Weight

200 mm
15,3 kg

