



L7104

**Dual Voice Coil
Subwoofer 25 cm**

Power Handling
750 Watts RMS / 1500 Watts Max.

Technical Specifications

Impedance	Zn	2 x 4 Ohms
Voice Coil Diameter	Ø	61 mm
Max. Linear Excursion	Xmax	+/- mm
Cone Area	Sd	439 cm ²
Moving Mass	Mms	g
DC Resistance	Re	2 x 3,9 Ohms
Resonance Frequency	Fs	37,5 Hz
Mechanical Q-Factor	Qms	9,791
Electrical Q-Factor	Qes	0,535
Total Q-Factor	Qts	0,507
Equivalent Air Volume	VAS	28,3 L
VC Inductance	Le	mH
Flux Density	B/L	N/A
Efficiency 1W/1m	SPL	85,9 dB

Recommended Enclosure

Ported Box	
Vented Volume:	63,7 L
Port Area:	220 cm ²
Port Length:	46 cm

Recommended Enclosure

Ported Box	
Vented Volume:	35,4 L
Port Area:	185 cm ²
Port Length:	50 cm

Mechanical Components

- Diecast Aluminium Basket
- Polypropylene Cone
- Santoprene Surround
- Single Nomex Spider
- Dual Magnet 2 x 59,1 oz (3.351 g)
- Magnet Size: Ø169 x 40 mm
- TIL (Glass-Fibre) Voice Coil

Dimensions & Weight

External Diameter:	272 x
Mounting Diameter:	272 mm
Mounting Depth:	237 x
Shipping Weight:	237 mm





L7104

**Dual Voice Coil
Subwoofer 25 cm**

Power Handling
750 Watts RMS / 1500 Watts Max.

Technical Specifications

Impedance	Zn	2 x 4 Ohms
Voice Coil Diameter	Ø	61 mm
Max. Linear Excursion	Xmax	+/- mm
Cone Area	Sd	439 cm ²
Moving Mass	Mms	g
DC Resistance	Re	2 x 3,9 Ohms
Resonance Frequency	Fs	37,5 Hz
Mechanical Q-Factor	Qms	9,791
Electrical Q-Factor	Qes	0,535
Total Q-Factor	Qts	0,507
Equivalent Air Volume	VAS	28,3 L
VC Inductance	Le	mH
Flux Density	B/L	N/A
Efficiency 1W/1m	SPL	85,9 dB

Recommended Enclosure

Ported Box	
Vented Volume:	63,7 L
Port Area:	220 cm ²
Port Length:	46 cm

Recommended Enclosure

Ported Box	
Vented Volume:	35,4 L
Port Area:	185 cm ²
Port Length:	50 cm

Mechanical Components

Former

Dimensions & Weight

175 mm
12,8 kg



Audio Design. Tel. 07253-9465-14. Fax 946510. eMail: boxes@audiodesign.de. Internet: www.audiodesign.de